

# Inductive Charging System





## Inductive Charging System


This new inductive charging solution consists of a primary and secondary coil system. Each coil system comprises several coils which are separately available for the optimal charging constellation.



## High Position Tolerance


- Nine coils in two layers fit into a standardized license plate
- Orthogonal alignment between primary and secondary coil system
- Five primary (stationary) and nine secondary (mobile) coils lead to an effective charging area of 0.9 x 0.5 m<sup>2</sup>

Characteristic coupling factor map




- Comparatively high coupling factors within the charging area

### Case I



### Case II



## Technical Data

<b>Nominal output power</b>	3,5 kW
<b>Efficiency (DC/DC)</b>	> 95%
<b>Operating frequency</b>	≤150kHz

## System Advantages

- **High transfer efficiency** and **small stray fields** through minimal air gap
- High **interoperability** through orthogonal alignment
- **High positioning tolerance**
- **Lightweight** pick-up
- Coils **fit in** conventional and standardized **license plate dimension**
- **Minimal package** volume compared to underbody systems
- No moving parts
- **Bidirectional** operation mode
- Further efficiency improvement through **wide band gap devices**

## Contact Us!

The Fraunhofer IISB is your research and development partner for inductive power transfer.

**We develop and realize complete inductive power transfer systems. From the FEM-Simulation, over power electronics analysis/simulation and mechanical integration to the realization of complete demonstrators.**

### Fraunhofer Institute for Integrated Systems and Device Technology IISB

Schottkystrasse 10  
91058 Erlangen, Germany

#### Contact

Christopher Joffe  
Tel.: +49 9131 761-296  
christopher.joffe@iisb.fraunhofer.de

www.iisb.fraunhofer.de